



Cirrus & Cirrus Rock 2017 Model

The space-saver, wall mounted Cirrus sauna heater is now with improved design and better performance.

Cirrus produces a well distributed heat from the floor up to the ceiling. Water thrown in front of the heater runs through the pockets of the carved soapstone and then converted into pleasant steam.

Cirrus Rock is the full sauna stone version of Cirrus. Cirrus Rock is now with more sturdy stainless rods that hold up to 60 kg of sauna stones. Water thrown into the heater evaporate well when it touches the exposed heated stones in the front.

The Cirrus heater is best for those who wants to have a hotter sauna room temperature while Cirrus Rock is for those who enjoy a mild and long lasting steam. Both heaters are available with built-in control and separate control unit.

Cirrus and Cirrus Rock heaters can be installed in **Tandem Connection*. **Tandem connection is connecting two heaters into a single control unit. User may pair Cirrus heaters to double the heating output.*



CIR2



CIR3



CRR2



CRR3



Normal kilowatt for Cirrus and Cirrus Rock heaters are 3, 4, 4.5, 5, 6, 7.5 and 9kW. When in Tandem connection are 6, 8, 9, 10, 12, 15 and 18kW.



Cirrus (CIR)



Cirrus Rock (CRR)

www.sawo.com



Technical Data

HEATER MODEL	kW	SAUNA ROOM		SIZE OF HEATER			STONES (kg)	SOAPSTONES (kg)	CONTROL
		MIN	MAX	WIDTH	DEPTH	HEIGHT			
CIR2-30NB/CIR2-30NS	3.0	2	4	410	210	970	6	23	built-in/separate
CIR2-40NB/CIR2-40NS	4.0	3	6	410	210	970	6	23	built-in/separate
CIR3-45NB/CIR3-45NS	4.5	3	6	570	210	970	10	34	built-in/separate
CIR2-50NB/CIR2-50NS	5.0	4	8	410	210	970	6	23	built-in/separate
CIR2-60NB/CIR2-60NS	6.0	5	8	410	210	970	6	23	built-in/separate
CIR3-60NB/CIR3-60NS	6.0	5	9	570	210	970	10	34	built-in/separate
CIR3-75NB/CIR3-75NS	7.5	7	12	570	210	970	10	34	built-in/separate
CIR3-90NB/CIR3-90NS	9.0	8	14	570	210	970	10	34	built-in/separate
CRR2-30NB/CRR2-30NS	3.0	2	4	410	240	970	40	-	built-in/separate
CRR2-40NB/CRR2-40NS	4.0	3	6	410	240	970	40	-	built-in/separate
CRR3-45NB/CRR3-45NS	4.5	3	6	570	240	970	65	-	built-in/separate
CRR2-50NB/CRR2-50NS	5.0	4	8	410	240	970	40	-	built-in/separate
CRR2-60NB/CRR2-60NS	6.0	5	8	410	240	970	40	-	built-in/separate
CRR3-60NB/CRR3-60NS	6.0	5	9	570	240	970	65	-	built-in/separate
CRR3-75NB/CRR3-75NS	7.5	7	12	570	240	970	65	-	built-in/separate
CRR3-90NB/CRR3-90NS	9.0	8	14	570	240	970	65	-	built-in/separate